



Applicable Requirements :  
ANSI/UL 1017  
CSA C22.2 No.243

### Characteristics



Stainless  
General



SD Tools &  
Accessories



HEPA -  
Included



High Filtration  
Efficiency Unit



Dry Recovery



3D Printing



Brushless  
Motor Available



- Ideal for housekeeping and general cleaning
- Complies with NFPA 652 paragraph 8.4.2.2.1.7 (1) to (7)
- Protected against ingress of dust
- HEPA filter with an efficiency of 99.995% on 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 2 x H14 HEPA filters
- For dry recovery only
- Disposable collection bag (conductive) - included
- Stainless steel tank SAE 430 fits any application
- Filter blockage indicator light
- Includes a complete static dissipative tool kit

## Specifications

2D-10 (4W) HEPA ORDLOC-652 W/3D TOOL KIT	113185A-3D	113185A-BL3D
<b>Model Name</b>	2D-10 (4W) HEPA ORDLOC-652 W/3D TOOL KIT	2D-10 (4W) HEPA ORDLOC-652 W/BRUSHLESS MOTOR W/3D TOOL KIT
<b>Type (Powerhead)</b>	Electric	Electric
<b>Voltage</b>	120 V	120 V
<b>Hertz</b>	60 Hz	60 Hz
<b>Phase</b>	Single	Single
<b>Wattage</b>	1207 W	1100 W
<b>Power</b>	1.6 HP	1.3 HP
<b>Amperage</b>	10.5 A	13 A
<b>Air Flow</b>	110 CFM	127 CFM
<b>Vacuum Pressure</b>	107 " H <sub>2</sub> O	89 " H <sub>2</sub> O
<b>Sound Level</b>	75 dB(A)	75 dB(A)
<b>Plug Type</b>	120V	120V
<b>Suction Inlet</b>	60 mm	60 mm
<b>Cart Type</b>	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
<b>Dry Recovery - Disposable Filter Bag</b>	5 gal.	5 gal.
<b>Length</b>	17 "	17 "
<b>Width</b>	17 "	17 "
<b>Height</b>	34 "	35 "
<b>Cord Length</b>	35 ft.	35 ft.

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



Upstream HEPA Filter - Included



Conductive Recovery Bags - included



3D Tool Kit for 60mm suction inlet - included



Optional 3D Tools