



CD-EX Models Certified for:
Division 1, Class I, Group D and Class II, Groups F and G, T3C
Division 1, Class II Group E (metal dust) motor and switch available
Division 2, Class I Group D and Class II, Groups F and G, T3C



CD EX Series IECEx 3rd Party Certified
Ex d IIB T4 Gb
Ex t IIIC T135°C Db IP65
IECEx LCI 10.0040 X
Certified for providing an Equipment Protection Level of EPL Db and EPL Gb



GUARANTEED for the Safe Recovery of Combustible/Conductive Dusts and Flammable Liquids

Characteristics



Continuous Duty



EX Certified



SS 304



Wet Recovery



Less than 10 ohms



Activated Carbon



Hydrocart



- Legally certified explosion proof/dust ignition proof
- Less than 10 ohms of resistivity
- Continuous duty 3-phase (TEFC) explosion proof/dust ignition proof motor. Third Party Certified
- For fuel, oil, and solvent recovery
- Equipped with a Middle Ring with Activated Carbon (MRAC) for the adsorption of toxic/noxious fumes and vapors
- Carbon cartridge contains 18 lb (8 kg) of activated carbon pellets. Different types of activated carbon are available
- Equipped with a heavy duty powder coated hydraulic cart for easy emptying of recovered material. Cart has static dissipative or conductive wheels
- Motor and switch for use in the presence of conductive metal dust is available. North-America: Class II, Group E Europe: Dust Group IIIC
- Other motor performances available

Specifications

CD-25 EX MRAC (HY-C)	112600A1	112600A2	112600A5
Model Name	CD-25 EX MRAC (HY-C)	CD-25 EX MRAC (HY-C)	CD-25 EX MRAC (HY-C)
Type (Powerhead)	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes
Voltage	460 V	230 V	575 V
Hertz	60 Hz	60 Hz	60 Hz
Phase	Three	Three	Three
Wattage	1480 W	1480 W	1480 W
Power	2 HP	2 HP	2 HP
Amperage	2.6 A	5.2 A	2.1 A
Air Flow	158 CFM	158 CFM	158 CFM
Vacuum Pressure	130 " H ₂ O	130 " H ₂ O	130 " H ₂ O
VRV Setting	80 " H ₂ O	80 " H ₂ O	80 " H ₂ O
Plug Type	Not Included	Not Included	Not Included
Suction Inlet	1.5 "	1.5 "	1.5 "
Cart Type	Hydro Cart (HYC)	Hydro Cart (HYC)	Hydro Cart (HYC)
Filter Cleaning	None	None	None
Dry Recovery - Tank	15 Gal	15 Gal	15 Gal
Liquid Recovery Capacity	17 gal.	17 gal.	17 gal.
Length	53 "	53 "	53 "
Width	20 "	20 "	20 "
Height	60 "	60 "	60 "
Weight (Vacuum Only)	448 lb.	448 lb.	448 lb.
Cord Length	50 ft.	50 ft.	50 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Activated Carbon Cartridge - Included



Nitrile Suction Hose - Included



Stainless Steel Mesh Filter - Included



Strainer Basket for TE Series - Included