

CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS

All the electrical components are certified by an NRTL such as UL, CSA or ETL



Characteristics



Continuous
Duty



Wet and Dry
Recovery



Detachable
Tank



SS 430



HEPA Filter
Available

HEPA - Optional

- Low cost vacuum system for continuous duty
- Available in Single or 3-phase configurations
- Regenerative blower with TEFC induction motor rated for continuous duty
- Very powerful machine
- Main filter with Manual Filter Shaker (MFS)
- Upstream filter cartridge for fine dust
- HEPA Filter with a minimum efficiency of 99.97% at 0.3 micron (installed in the place of the upstream filter cartridge) - optional
- Stainless steel SAE 430 filter chamber and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Standard configuration is for dry recovery only. Optional floater (liquid cut-off) is available for liquid recovery. Floater is installed in the place of the cyclonic separator
- Basic tool kit included

Specifications

PLANET 140 GL	111210A1	111210A5
Model Name	PLANET 140 GL	PLANET 140 GL
Type (Powerhead)	Electric	Electric
TEFC Motor	Yes	Yes
Voltage	460 V	575 V
Hertz	60 Hz	60 Hz
Phase	Three	Three
Wattage	4000 W	4000 W
Power	5.5 HP	5.5 HP
Amperage	6.6 A	N/A A
Air Flow	194 CFM	194 CFM
Vacuum Pressure	118 " H ₂ O	118 " H ₂ O
Sound Level	73 dB(A)	73 dB(A)
Plug Type	Not Included	Not Included
Suction Inlet	60 mm	60 mm
Cart Type	Detachable Tank (DT)	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
Filter Type	HEPA H14	HEPA H14
Filter Surface Area	15 ft ²	15 ft ²
Dry Recovery - Tank	15.6 Gal	15.6 Gal
Liquid Recovery Capacity	15.6 gal.	15.6 gal.
Filter Efficiency	99.97	99.97
Particle Size	0.3	0.3
Weight (Vacuum Only)	160 lb.	160 lb.
Cord Length	30 ft.	30 ft.
Container Material	430 Stainless Steel	430 Stainless Steel
Container Diameter	16.5 "	16.5 "

Please note that specifications are subject to change without notice

Use only recommended tools & accessories




Detachable Exhaust Silencer (GL Series)



Floater (Liquid Cut-Off) (GL Series) - Optional



Side view of Detachable Tank (GL Series)



Filter Cartridge (GL Series)



Polyester Main Filter (GL Series)



Suction Inlet, 60mm, Aluminum (GL Series)



Top Mounted Filter Shaker (GL Series)



Basic Tool Kit (GL Series) - Included



Cyclonic Separator (GL Series) - Included