

CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS

All the electrical components are certified by an NRTL such as UL, CSA or ETL



Characteristics



- HEPA filter with an efficiency of 99.995% on 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- ULPA filter with an efficiency of 99.999% on 0.12 micron. Filtration efficiency of 99.9995% on 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - optional
- Cleanroom compatible with ISO Class 4 (former Class 10)
- Designed to be attached to process machines and for general cleanup in the Food industry
- Can also be used for the recovery of tablets in the Pharmaceutical industry
- Continuous duty single phase or 3-phase motor mounted vertically
- Includes disposable filter bags
- Available in a fixed or mobile unit
- For dry recovery only
- Available in stainless steel, white powder coated or stainless steel & white powder coated versions
- Vertical mounting for areas with space constraints
- 4 wheels for easy maneuverability

Specifications

CD-1500 CR (PFB) SERIES	111574A1	111574A2	111574A3	111574A4	111578A1	111578A2
Model Name	CD-1500 CR (PFB) - P/C & S/S	CD-1500 CR (PFB) - P/C & S/S	CD-1500 CR (PFB) - P/C & S/S	CD-1500 CR (PFB) - P/C & S/S	CD-1500 CR (PFB) - STAINLESS STEEL	CD-1500 CR (PFB) - STAINLESS STEEL
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes	Yes
Voltage	460 V	230 V	120 V	230 V	460 V	230 V
Hertz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Three	Three	Single	Single	Three	Three
Wattage	850 W	850 W	850 W	850 W	850 W	850 W
Power	1.1 HP	1.1 HP	1.1 HP	1.1 HP	1.1 HP	1.1 HP
Amperage	2.1 A	3.6 A	14 A	7 A	2.1 A	3.6 A
Air Flow	95 CFM	95 CFM	95 CFM	95 CFM	95 CFM	95 CFM
Vacuum Pressure	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O
VRV Setting	70 " H ₂ O	70 " H ₂ O	70 " H ₂ O	70 " H ₂ O	70 " H ₂ O	70 " H ₂ O
Sound Level	64 dB(A)	64 dB(A)	64 dB(A)	64 dB(A)	64 dB(A)	64 dB(A)
Plug Type	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
Suction Inlet	2 "	2 "	2 "	2 "	2 "	2 "
Cart Type	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	None	None	None	None	None	None
Dry Recovery - Tank	5 Gal	5 Gal	5 Gal	5 Gal	5 Gal	5 Gal
Dry Recovery - Disposable Filter Bag	4 gal.	4 gal.	4 gal.	4 gal.	4 gal.	4 gal.
Length	13.5 "	13.5 "	13.5 "	13.5 "	13.5 "	13.5 "
Width	19.5 "	19.5 "	19.5 "	19.5 "	19.5 "	19.5 "
Height	37 "	37 "	37 "	37 "	37 "	37 "
Weight (Vacuum Only)	125 lb.	125 lb.	125 lb.	125 lb.	108 lb.	108 lb.
Cord Length	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.
CD-1500 CR (PFB) SERIES	111578A3	111578A4				
Model Name	CD-1500 CR (PFB) - STAINLESS STEEL	CD-1500 CR (PFB) - STAINLESS STEEL				
Type (Powerhead)	Electric	Electric				
TEFC Motor	Yes	Yes				
Voltage	120 V	230 V				
Hertz	60 Hz	60 Hz				
Phase	Single	Single				
Wattage	850 W	850 W				
Power	1.1 HP	1.1 HP				

Amperage	14 A	7 A
Air Flow	95 CFM	95 CFM
Vacuum Pressure	110 " H ₂ O	110 " H ₂ O
VRV Setting	70 " H ₂ O	70 " H ₂ O
Sound Level	64 dB(A)	64 dB(A)
Plug Type	Not Included	Not Included
Suction Inlet	2 "	2 "
Cart Type	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	None	None
Dry Recovery - Tank	5 Gal	5 Gal
Dry Recovery - Disposable Filter Bag	4 gal.	4 gal.
Length	13.5 "	13.5 "
Width	19.5 "	19.5 "
Height	37 "	37 "
Weight (Vacuum Only)	108 lb.	108 lb.
Cord Length	50 ft.	50 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Clear Polyliner Recovery Bags - Included



Disposable Filter Bag - Included



Tools and Accessories (Toolkit 4B) - Optional