



DUST IGNITION PROTECTED
Division 2, Class II, Groups F and G



Groups F and G Cleanroom Compatible Dust (Combustible and Toxic/Nuisance)
IIIB Cleanroom Compatible Dust (Combustible and Toxic/Nuisance)

ESD Safe Vacuum Cleaners for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

Characteristics



ULPA - Included



High Filtration Efficiency Unit



Static Dissipating



Stainless General



SD Accessories - Included



Dry Recovery



- Long lasting brushless motor rated for continuous duty
- For housekeeping and general cleaning
- EMI/RFI shielded and ESD safe
- 5-stage filtration system, includes dual ULPA filters (U15) (one for the working air and one for the cooling air), double cloth filter, and disposable filter bags
- Includes an indicator light to warn of vacuum blockage
- Designed to be autoclavable - stainless steel SAE 316 electropolished (except motor housing)

Specifications

CWR-10 EX (4W) BLS D	110540A-BLS D
Model Name	CWR-10 EX (4W) BLS D
Type (Powerhead)	Electric
Voltage	120 V
Hertz	60 Hz
Phase	Single
Wattage	1100 W
Power	1.3 HP
Amperage	13 A
Air Flow	127 CFM
Vacuum Pressure	89 " H ₂ O
Sound Level	75 dB(A)
Plug Type	120V
Suction Inlet	1.5 "
Cart Type	4 Wheel Dolly (4W)
Filter Cleaning	None
Dry Recovery - Disposable Filter Bag	5 gal.
Length	30 "
Width	19 "
Height	25 "
Weight (Vacuum Only)	66 lb.
Cord Length	35 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Conductive Recovery Bags - included



CWR EX Tools and Accessories - Included