



Applicable Requirements :  
ANSI/UL 1017  
CSA C22.2 No.243

### Characteristics



HEPA Filter Available

HEPA - Optional



Detachable Tank



Dry Recovery



Dual Motor



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- For general housekeeping
- Dual bypass/dual speed heavy duty motors. 2000W (2400 max.)
- Manual Filter Shaker (MFS) system
- For dry recovery only
- Stainless steel SAE 430 body and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels

## Specifications

4D-55L (DT) HD MFS SERIES	112109A	112110A
<b>Model Name</b>	4D-55L (DT) HD MFS NO HEPA	4D-55L (DT) HD MFS HEPA
<b>Type (Powerhead)</b>	Electric	Electric
<b>Voltage</b>	120 V	120 V
<b>Hertz</b>	60 Hz	60 Hz
<b>Phase</b>	Single	Single
<b>Wattage</b>	2040 W	2040 W
<b>Power</b>	2.7 HP	2.7 HP
<b>Amperage</b>	17 A	15.2 A
<b>Air Flow</b>	200 CFM	200 CFM
<b>Vacuum Pressure</b>	90 " H <sub>2</sub> O	90 " H <sub>2</sub> O
<b>Sound Level</b>	78 dB(A)	78 dB(A)
<b>Plug Type</b>	Not Included	Not Included
<b>Suction Inlet</b>	2 "	2 "
<b>Cart Type</b>	Detachable Tank (DT)	Detachable Tank (DT)
<b>Filter Cleaning</b>	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
<b>Dry Recovery - Tank</b>	14.5 Gal	14.5 Gal
<b>Length</b>	23 "	23 "
<b>Width</b>	21 "	21 "
<b>Height</b>	55 "	55 "
<b>Weight (Vacuum Only)</b>	91 lb.	91 lb.
<b>Cord Length</b>	35 ft.	33 ft.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



55L Detachable Recovery Tank



HEPA Filter - Included



Ø1.5" (Ø38mm) Static Dissipative Tools and Accessories - Optional



Ø2" (Ø50mm) Static Dissipative Tools and Accessories - Optional



Clear Polyliner Recovery Bags - Optional