



Applicable requirements :
Standard(s) for Electric Vacuum Cleaning Machines and Blower Cleaners (UL-1017)

Characteristics



HEPA -
Included



High Filtration
Efficiency Unit



Wet and Dry
Recovery



Accessories
Included



Low Noise



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Designed for the recovery of asbestos, lead, mold, etc.
- Lightweight and portable
- Heavy duty 2-stage by-pass motor
- 4-stage filtration system
- For wet & dry recovery
- Heavy duty plastic recovery tank
- Stainless steel recovery tank available
- Ready to use - filters and tool kit included
- Mounted on a 4-Wheel Dolly for easy maneuverability
- 1260W motor and 50' grounded power cord available
- Carriage base with accessories tray available

Specifications

ASL-10 HEPA MR	111856A
Model Name	ASL-10 HEPA MR
Type (Powerhead)	Electric
Voltage	120 V
Hertz	60 Hz
Phase	Single
Wattage	996 W
Power	1.3 HP
Amperage	8.3 A
Air Flow	96 CFM
Vacuum Pressure	99 " H ₂ O
Sound Level	62 dB(A)
Plug Type	120V
Suction Inlet	1.5 "
Cart Type	4 Wheel Dolly (4W)
Filter Cleaning	None
Dry Recovery - Tank	2.6 Gal
Dry Recovery - Disposable Filter Bag	2.5 gal.
Liquid Recovery Capacity	2.6 gal.
Length	16 "
Width	16 "
Height	28 "
Weight (Vacuum Only)	25.5 lb.
Cord Length	33 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Beater Bar - Optional



HEPA Filter - Included



AS-10 Tools and Accessories (Wet & Dry) - Included