



CE EX II 3D
Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X

LCIE 19 ATEX 1001 X



IECEx 3rd Party Certified

Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X
IECEx LCIE 15.0048



This model can be used to Recover Combustible Dusts such as Dust Groups :

IIIA Combustible Flyings (lints of cotton, wood chips, etc.)
IIIB Non-Conductive Dusts (flour dust, grain dust, flour, sugar, starch, wood, plastic, carbonaceous dusts, coal, carbon black)
IIIC Conductive Dusts (combustible metal dust, aluminum, magnesium, commercial alloys)

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Characteristics



Static Dissipating



HEPA - Included



High Filtration Efficiency Unit



Stainless General



SD Tools & Accessories



Dry Recovery



EX Certified



3D Printing



High Efficiency Cyclone



Brushless Motor Available

- Powder Recovery System (PRS) for 3D Printing and Additive Manufacturing
- Suitable for all AM applications (both plastic & metal)
- Facilitates the extraction & recovery of powder from the AM machine powder bed and build chamber
- The integrated cyclonic pre-separator can separate and collect up to 98% of the powder before it enters the vacuum
- The powder is recovered in the detachable recovery tank made of stainless steel Type 304
- Recovered powder can be easily disposed or re-used depending on the application
- Meets NFPA 484 for Powder and Dust Collection paragraph 11.2.4.4.1 – Cyclone without filter media
- ATEX & IECEx Certified for Conductive dusts Group IIIC
- Provides a very high protection level in the collection tank

Specifications

C-10 EX DT (PRS-HEC) WITH 3D TOOL KIT	113230B-3D	113230B-BL3D
Model Name	C-10 EX DT (PRS-HEC) WITH 3D TOOL KIT	C-10 EX DT (PRS-HEC) BLSD WITH 3D TOOL KIT
Type (Powerhead)	Electric	Electric
Tension	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz
Phase	Single	Single
Wattage	1200 W	1100 W
Power	1.2 kW	1.1 kW
Amperage	5 A	8 A
Air Flow	194 m ³ /h	215 m ³ /h
Vacuum Pressure	2504 mm H ₂ O	2250 mm H ₂ O
Sound Level	72 dB(A)	72 dB(A)
Type of Power Outlet	Not Included	Not Included
Recovery Capacity (Tank)	25 L	25 L
Cord Length	10 m	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



C-10 EX DT (PRS-HEC) - Side View 1



C-10 EX DT (PRS-HEC) - Side View 2



3D Tool Kit for 2" camlock suction inlet - included



Optional 3D Accessories



Extra recovery tank with lid to facilitate the refresh and re-use of the recovered powders (Part# 223001-ASM1) - Optional



Longer Life Brushless Motor Available (always with 4 x H14 HEPA filters)