



Meets EU Safety, Health and Environmental Protection Requirements

Characteristics



Coalescing Filter Element



SD Accessories - Included



SS 304




Dry Recovery



HEPA - Included



High Filtration Efficiency Unit



Wet Mix - Water



Less than 10 ohms



3D Printing



Brushless Motor Available



- For the safe collection of combustible dusts in ordinary locations/areas and unclassified zones
- Ignition source safe/protected
- Protected against ingress of dust IP5X
- Very high level of protection inside the collection tank
- Immersion separator "Wet Mix". For use with water (no oil)
- Designed for the recovery and INERTIZATION of combustible dust into a liquid immersion bath
- Electric
- Dual HEPA filters H14 (upstream and downstream)
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency at 0.3 micron
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 2 x H14 HEPA filters
- Recovery tank made of stainless steel SAE Type 304
- Filter blockage indicator light
- Disposable collection bag (conductive) - included
- Recovery capacity - 3.25 gal. (12.3L) of water is required in the recovery tank. The conductive "wet" recovery bag has a recovery capacity of 3L (0.8 gal)
- Degassing vent allows gas to be evacuated automatically from the unit
- Equipped with a liquid level indicator
- Includes a complete static dissipative tool kit

Specifications

2D-10 (IT-40L) CFE HEPA ORDLOC SERIES W/3D TOOL KIT	113186B-3D
Model Name	2D-10 (IT-40L) CFE HEPA ORDLOC SERIES
Type (Powerhead)	Electric
Tension	220-240 V
Frequency	50/60 Hz
Phase	Single
Wattage	1200 W
Power	1.2 kW
Amperage	5 A
Air Flow	194 m ³ /h
Vacuum Pressure	2504 mm H ₂ O
Sound Level	75 dB(A)
Type of Power Outlet	Not Included
Suction Inlet	38 mm
Cart Type	4 Wheel Dolly (4W)
Filter Cleaning	Liquid Immersion Bath
Length	48 cm
Width	46 cm
Height	86 cm
Cord Length	10 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Liquid Level Indicator and Drain Valve - Included



A Conductive "Wet" Recovery Bag can be used in conjunction with the Immersion Bath to facilitate material recovery and emptying



Coalescing HEPA filter (Upstream) - Included



Degassing Vent - Included



3D Tool Kit for 1.5" camlock suction inlet - included



Optional 3D Tools



#228093 - Depressor cage for conductive wet recovery bag - optional