


Characteristics



Hydrocart



Activated Carbon



Corrosive Recovery



Accessories Included



Wear Protective Clothing (PPE)



Wet Recovery



- Can be used in the Pharmaceutical industry when equipped with a stainless steel SAE 304 4-wheel dolly or tilting cart
- Designed for the recovery of acids and corrosive liquids
- Heavy duty 2-stage by-pass motor
- Available with a variety of activated carbon, including KINA 3® activated carbon for the adsorption of chloride and acid vapors (HF, HCL, etc). Other types of activated carbon are available. Carbon cartridges must be ordered separately - not included
- For liquid recovery
- Acid-resistant polyethylene, nylon and PVC
- Available with a 4-wheel dolly, tilting cart, or hydro-cart
- 4-wheel dolly, and tilting cart available in stainless steel
- Includes a complete tool kit.

Specifications

2D-ARU-15 SERIES	111429B	111429C	111429D	111429E	111430B	111430C
Model Name	2D-ARU-15 (TC) MRAC	2D-ARU-15 (TC) MRAC	2D-ARU-15 (TC) MRAC	2D-ARU-15 (TC) MRAC	2D-ARU-15 STD (HY-C) MRAC	2D-ARU-15 STD (HY-C) MRAC
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
Voltage	240 V	240 V	240 V	240 V	240 V	240 V
Hertz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Phase	Single	Single	Single	Single	Single	Single
Wattage	1050 W	1050 W	1050 W	1050 W	1050 W	1050 W
Power	1 kW	1 kW	1 kW	1 kW	1 kW	1 kW
Amperage	5 A	5 A	5 A	5 A	5 A	5 A
Air Flow	173 m ³ /h	173 m ³ /h	173 m ³ /h	173 m ³ /h	173 m ³ /h	173 m ³ /h
Vacuum Pressure	2110 mm H ₂ O	2110 mm H ₂ O	2110 mm H ₂ O	2110 mm H ₂ O	2110 mm H ₂ O	2110 mm H ₂ O
Plug Type	European	UK	Swiss	Chinese	European	UK
Suction Inlet	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
Cart Type	Tilt Cart (TC)	Tilt Cart (TC)	Tilt Cart (TC)	Tilt Cart (TC)	Hydro Cart (HYC)	Hydro Cart (HYC)
Filter Cleaning	None	None	None	None	None	None
Liquid Recovery Capacity	47.3 L	47.3 L	47.3 L	47.3 L	47.3 L	47.3 L
Length	69 cm	69 cm	69 cm	69 cm	124 cm	124 cm
Width	76 cm	76 cm	76 cm	76 cm	51 cm	51 cm
Height	122 cm	122 cm	122 cm	122 cm	130 cm	130 cm
Weight (Vacuum Only)	48 kg.	48 kg.	48 kg.	48 kg.	113 kg.	113 kg.
Cord Length	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m
2D-ARU-15 SERIES	111430D	111430E				
Model Name	2D-ARU-15 STD (HY-C) MRAC	2D-ARU-15 STD (HY-C) MRAC				
Type (Powerhead)	Electric	Electric				
Voltage	240 V	240 V				
Hertz	50 Hz	50 Hz				
Phase	Single	Single				
Wattage	1050 W	1050 W				
Power	1 kW	1 kW				
Amperage	5 A	5 A				
Air Flow	173 m ³ /h	173 m ³ /h				
Vacuum Pressure	2110 mm H ₂ O	2110 mm H ₂ O				
Plug Type	Swiss	Chinese				
Suction Inlet	38 mm	38 mm				
Cart Type	Hydro Cart (HYC)	Hydro Cart (HYC)				
Filter Cleaning	None	None				
Liquid						

Recovery Capacity	47.3 L	47.3 L
Length	124 cm	124 cm
Width	51 cm	51 cm
Height	130 cm	130 cm
Weight (Vacuum Only)	113 kg.	113 kg.
Cord Length	10.6 m	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



ARU STD Tools and Accessories - Included



Activated Carbon Cartridge - Optional



Liquid Filter - Included



2D-ARU-15 STD (HY-C) MRAC