



CD-EX Models Certified for:

Class I, Division 1, Group D T3C and Class II, Division 1, Groups F and G

Class II, Division 1, Group E (metal dust) motor and switch available

Class I, Division 2, Group D and Class II, Division 2, Groups F and G



CD EX Series IECEx 3rd Party Certified

Ex d IIB T4 Gb

Ex t IIIC T135°C Db IP65

IECEx LCI 10.0040

Certified for providing an Equipment Protection Level of EPL Db and EPL Gb



GUARANTEED for the Safe Recovery of Combustible/Conductive Dusts

ESD Safe Vacuum Cleaners for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Characteristics



ULPA - Included



Continuous Duty




Explosion Proof



SS 304



Dry Recovery



Less than 10 ohms

- Legally certified explosion proof/dust ignition proof.
- Less than 10 Ohms of resistivity.
- ULPA Filter - With an efficiency of 99.999% on 0.12 micron. Filtration efficiency of 99.9995% on 0.18 micron. Tested: IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility - Included
- Includes a muffler for noise reduction.
- Available with a Conductive Filter Bag (CFB) or Manual Reverse Purge with Filter Tubes (MRPFT) system
- Designed to be attached to process machines and for general cleanup
- Can also be used for the recovery of Tablets in the Pharmaceutical Industry.
- Continuous Duty Single Phase (TEFC) Explosion Proof/Dust Ignition Proof motor
- For dry recovery only
- All Stainless Steel SAE 304 construction
- Vertical mounting for areas with space constraints.
- SD* Polyliner and retainer clip included, for the easy and safe disposal of recovered materials.
- Includes a complete static dissipative tool kit
- Motor and switch for use in presence of conductive metal dusts available. North-America: Class II, Group E; Europe: Dust group IIIC
- Other motor performances available.

Specifications

CD-120V EX PHARMA SERIES	112163A3	112176A3
Model Name	CD-120V EX (CFB) PHARMA - CLASS I - GROUP D, CLASS II - GROUPS F & G	CD-120V EX (MRPFT) PHARMA - CLASS I - GROUP D, CLASS II - GROUPS F & G
Type (Powerhead)	Electric	Electric
TEFC Motor	Yes	Yes
Voltage	120 V	120 V
Hertz	60 Hz	60 Hz
Phase	Single	Single
Wattage	750 W	750 W
Power	1 HP	1 HP
Amperage	13.5 amps.	13.5 amps.
Air Flow	110 CFM	110 CFM
Vacuum Pressure	110 " H ₂ O	110 " H ₂ O
VRV Setting	65 " H ₂ O	65 " H ₂ O
Sound Level	68 dB(A)	68 dB(A)
Plug Type	Not Included	Not Included
Suction Inlet	2 "	2 "
Cart Type	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	Conductive Filter Bag (CFB)	Manual Reverse Purge with Filter Tubes (MRPFT)
Dry Recovery - Tank	13.2 Gal	13.2 Gal
Length	27 "	27 "
Width	19 "	19 "
Weight (Vacuum Only)	211 lbs.	214 lbs.
Height	59 "	59.5 "
Cord Length	50 ft.	50 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Ø2" (Ø50mm) Static Dissipative Tools and Accessories - Included



Filter Tubes Assembly for MRPFT models - Included



Collection Filter Bag (CFB), Static Dissipative



CD-120V EX (CFB) PHARMA