

ATEX  CE  II 2D
Ex h IIIIC T85°C Db
For use in ATEX Zone 21 & Zone 22 (Dust) potentially explosive atmospheres



Characteristics



Static Dissipating



Cleanroom Compatible



Pharma Applications



Corrosive Recovery



Activated Carbon



Wet Recovery



Accessories Included



Wear Protective Clothing (PPE)

- Static dissipative and grounded
- Designed for the recovery of acids and corrosive liquids
- Certified for use in hazardous locations where flammable gases/vapors are present
- Pneumatic (air-operated)
- Available with a variety of activated carbon, including KINA 3® activated carbon for the adsorption of chloride and acid vapors (HF, HCL, etc). Other types of activated carbon are available. Carbon cartridges must be ordered separately - not included
- For liquid recovery
- Static dissipative acid resistant polyethylene, nylon and PVC
- Available with a 4-wheel dolly, tilting cart, or hydro-cart
- 4-wheel dolly, and tilting cart available in stainless steel
- Includes a complete static dissipative tool kit

Specifications

SS-ARU-15 EX (TC) MRAC	111437
Model Name	SS-ARU-15 EX (TC) MRAC
Type (Powerhead)	Pneumatic
Venturi	Single
Venturi (diam.)	6 mm
Minimum Compressor	15 HP
Air Line Size (Diam.)	1/2" (12.7mm)
Input Air Volume	21.2 L/s
Input Air Pressure	5.5 Bar
Air Flow	187 m ³ /h
Vacuum Pressure	4320 mm H ₂ O
Suction Inlet	38 mm
Cart Type	Tilt Cart (TC)
Filter Cleaning	None
Liquid Recovery Capacity	47.3 L

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



Liquid Filter - Included



ARU EX Tools and Accessories - Included



Activated Carbon Cartridge - Optional



Grounding reel with stainless steel housing and cable - Optional